

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
13 June 2002 (13.06.2002)

PCT

(10) International Publication Number
WO 02/47332 A2

(51) International Patent Classification⁷: **H04L 12/24**

(21) International Application Number: PCT/US01/45669

(22) International Filing Date: 5 December 2001 (05.12.2001)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
09/730,864 6 December 2000 (06.12.2000) US

(71) Applicant: **INTELLIDEN, INC.** [US/US]; 90 South
Casacade Avenue, Suite 500, Colorado Springs, CO 80903
(US).

(72) Inventors: **TINDAL, Glen**; 5331 Wells Fargo Drive, Col-
orado Springs, CO 80918 (US). **SCHENK, Jeffery, A.**; 996
Hartford Street, Cambia, CA 93428 (US).

(74) Agent: **PIETRANTONIO, Frank, V.**; Cooley Godward
LLP, Attn: Patent Group, 11951 Freedom Drive, One Free-
dom Square-Reston Town Center, Reston, VA 20190-5601
(US).

(81) Designated States (*national*): AE, AG, AI, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NO, NZ, PH, PL, PT, RO, RU, SD, SE, SG, SI,
SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA,
ZW.


(84) Designated States (*regional*): ARIPO patent (GI, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR,
GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent
(BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR,
NE, SN, TD, TG).

Published:

— without international search report and to be republished
upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: SYSTEM AND METHOD FOR CONFIGURATION, MANAGEMENT AND MONITORING OF NETWORK RE-
SOURCES



(57) Abstract: A method and apparatus to configure, monitor and manage network devices without regard for device type and/or manufacturer is disclosed. One implementation of this embodiment includes a network manager unit disposed between the network administrator and the network devices. The network manager unit allows the administrator to holistically view, configure and manage an entire network without regard to device type and/or manufacturer. The administrator can implement this holistic approach with the use of a central repository for all configuration information and/or central posting location for all network events.

WO 02/47332 A2

Best Available Copy

**SYSTEM AND METHOD FOR CONFIGURATION, MANAGEMENT
AND MONITORING OF NETWORK RESOURCES**

FIELD OF THE INVENTION

5 The present invention relates generally to network systems. More particularly, but not by way of limitation, the present invention relates to systems and methods for configuration, management and monitoring of network resources such as routers, optical devices and the like.

BACKGROUND OF THE INVENTION

10 With the ever-increasing reliance upon electronic data, businesses are becoming more and more reliant upon those networks responsible for distributing that data. Unfortunately, the rapid growth in the amount of data consumed by businesses has outpaced the development and growth of certain necessary network infrastructure components. One reason that the development and growth of the network
15 infrastructure has lagged behind centers on the present difficulty in expanding, configuring, and reconfiguring existing networks. Even the most routine network expansions and reconfigurations, for example, require significant, highly technical, manual intervention by trained network administrators. Unfortunately, these highly trained network administrators are in extremely short supply. Thus, many needed
20 network expansions and reconfigurations are delayed or even completely avoided

because of the inability to find the needed administrators to perform the required laborious, technical tasks.

The present difficulty in configuring and reconfiguring networks is best illustrated by an example directed toward installing a single new router on an existing network. To install a new router (such as router 100 or 105 in FIGURE 1), an administrator 110 first would need to choose a particular router with the best attributes for the network. The basic configuration of the new router generally will be defined by its manufacturer and its model. Although it would seem that the router should be chosen based upon its attributes, administrators 110 often choose a router based upon the identity of its manufacturer and the administrators' ability to configure devices from that manufacturer. Administrators 110, for example, may only know how to configure and operate devices manufactured by Cisco Systems, Inc. and may overlook equal or even superior devices from other manufacturers merely because they cannot configure them.

After the administrator 110 has chosen the desired router (router 105, for example), the administrator 110 generally will order the router 105 from the manufacturer and have it shipped, not necessarily to the installation site, but rather to the administrator's site where a basic configuration can be installed. The administrator 110 then ships the router 105 to the installation site where it can be physically installed. After the router 105 has been physically installed, the administrator 110 typically is manually notified, e.g., by telephone, that the router 105 is connected to the network. The administrator must then create the device-specific commands required to fully configure the router 105 and transfer those commands to the router's memory 115.

After the administrator 110 verifies that the device-specific commands were installed correctly, the router 105 can be brought online.

Obviously, the steps required for an administrator to configure a single router are quite cumbersome and require significant technical skill. The problem, however, is even more severe when the administrator desires to simultaneously configure or reconfigure several network devices. First, the administrator, for example, would need to manually identify the network devices that need to be configured or reconfigured. For example, if the administrator desired to turn up service between two points, the administrator would need to identify the routers along the path between the two points.

10 The administrator would then need to verify that the policies and rules established for the network permit the contemplated reconfiguration for those devices. Assuming that the reconfiguration is within the network's policies and rules, the administrator would need to create the device-specific code required to reconfigure each of the identified devices. In many instances, the same device-specific code cannot be used on all of the

15 devices. For example, the device-specific commands required to reconfigure a Cisco™ router differ significantly from the device-specific commands required to reconfigure a Juniper™ router. Thus, if the identified network devices include both Cisco™ and Juniper™ routers, the administrator would be required to create different versions of the device-specific commands, thereby significantly increasing the chance for error in

20 the reconfiguration process.

Once the device-specific commands have been created for each of the identified network devices, the commands must be manually transmitted to each device. That is, a connection, e.g., a telnet connection, must be established to each device and the

particular commands transferred thereto. After each device has received its commands, the network administrator must manually reconnect to each device and verify that the device received the proper commands and that it is operating properly.

Although some tools have been developed to help administrators perform
5 certain ones of the laborious tasks of network management, these tools are extremely limited in their application. For example, CiscoWorks™ is a group of unrelated tools that can aid administrators in some enterprise level tasks. CiscoWorks™ and similar tools provide singularly focused, unrelated tools to perform activities such as quality of service (QOS) provisioning and network policy management. These tools do not
10 provide a way to interrelate the various happenings in a network. In essence, these present network tools lack a holistic approach to network administration.

Moreover, tools like CiscoWorks™ are generally dedicated to the management of one type of network device, e.g., router or optical device, and one brand of network device. For example, CiscoWorks™ does not help an administrator configure a
15 Juniper™ router, and it does not help an administrator configure optical devices. Thus, if the network has both Cisco™ and Juniper™ devices, multiple, unrelated tools must be utilized to perform basic network management tasks. Unfortunately, because these multiple, unrelated tools are so difficult to manage, network administrators are prone to select routers based upon manufacturer identity rather than upon device features.

20 In addition to several other drawbacks, these singularly focused network tools result in substandard fault detection and recovery. For example, in present systems, once a configuration is changed, there is no easy way to "back out" of that

configuration if a problem arises. Presently, if a new configuration for a target device fails, the network administrator would be forced to recreate the device-specific commands of the target device's previous configuration, manually connect to the device and then transmit the recreated device-specific commands to the device. As can
5 be appreciated, this process can be extremely time consuming and error prone.

The lack of a comprehensive, holistic tool to manage network resources has led to slowed expansion and the under utilization of existing networks. As skilled administrators become more scarce and as networks grow larger and more complicated, the problems surrounding network management could reach crisis proportions.
10 Accordingly, an integrated network administration tool is needed. In particular, a system and method are needed to efficiently configure, monitor and manage network devices without regard for device type and/or manufacturer.

SUMMARY OF THE INVENTION

To remedy the above described and other deficiencies of the current
15 technology, a system and method for the configuration and monitoring of network devices has been developed. In one embodiment, the present invention provides a system and method to configure, monitor and/or manage network devices without regard to device type and/or manufacturer identity. One implementation of this embodiment includes a network manager unit disposed between the network
20 administrator and the network devices. The network manager unit allows the administrator to holistically view, configure and manage an entire network. That is, the administrator can view, configure and manage, for example, both optical devices and/or

routers without regard to manufacturer identity or specific model. The administrator can implement this holistic approach with the use of a central repository for all configuration information and/or a central posting location for all network events.

In one embodiment, for example, an administrator can configure a new
5 device or reconfigure an existing device by logging into the network manager unit and selecting a particular network device to configure. The network manager unit can then retrieve a configuration record unique to the selected network device from the common repository and provide that record to the administrator. After receiving the record, the administrator can change fields therein without regard for manufacturer identity of the
10 network device. Next, the network manager unit can automatically verify that the requested changes to the configuration record comply with the policies and rules established for the network, and assuming that the changes do not violate any of the policies or rules, the network manager unit can update and store the modified configuration record in the central repository. A copy of the old configuration record
15 can be kept in the central repository for fault recovery, modeling and other purposes.

Once the configuration record has been changed, network manager unit can use the fields of the modified configuration record to generate the actual device-specific commands needed to configure the selected network device. For example, the fields in the configuration record can be used to populate variable fields in a device-specific
20 code template. In such an embodiment, the administrator is not required to know or create the actual device-specific commands that are required to configure the selected network device. Instead, the administrator only needs to know the general objective

such as "enable router." The network manager unit will transform this general objective into the actual device-specific commands.

After the network manager unit has created the device-specific commands to match the altered configuration record, these commands are automatically pushed to the selected network device and stored in memory therein. A copy of those commands is also stored in association with the configuration record. Finally, after the new device-specific commands have been pushed to the selected network device, the network manager unit can verify the proper installation and operation of the new configuration information.

10 In essence, one embodiment of the present invention allows a configuration record to be created and/or modified for each network device regardless of the device's type, manufacturer or model. Each of the configuration records can be stored in a central repository for simplified access, retrieval and editing. Thus, to change the configuration for any network device, the network manager unit need only retrieve the altered configuration record from the central repository, generate the device-specific commands based upon that configuration record and push those generated device-specific commands to the target network device.

In another innovative aspect, the present invention enables automatically responses to network events. For example, network devices can be configured to post messages to a central posting location at the network manager unit. The network manager unit can read these posted network events from the central posting location and determine a proper response based upon predefined rules and policies. The

network manager unit can then automatically implement the response. For example, if a particular router becomes congested, that router can post a message to the central posting location. The network manager unit can then read that message and determine the appropriate response for the congested router. The policy could indicate, for example, that the router configuration should be changed to enable congestion handling features. The network manager unit, in this scenario, could automatically reconfigure the router to enable those congestion-handling features.

As can be appreciated by those skilled in the art, the present invention addresses the significant shortfalls in present network technology. In particular, the present invention, provides a holistically way to configure, manage and view an entire network system. These and other advantages of the present invention are described more fully herein.

BRIEF DESCRIPTION OF THE DRAWINGS

Various objects and advantages and a more complete understanding of the present invention are apparent and more readily appreciated by reference to the following Detailed Description and to the appended claims when taken in conjunction with the accompanying Drawings wherein:

FIGURE 1 illustrates a present system for configuring network routers;

FIGURE 2 illustrates a system for configuring network devices in accordance with the principles of the present invention;

FIGURE 3 illustrates in more detail the network manager unit shown in
FIGURE 2;

FIGURE 4 illustrates in more detail the directory element shown in FIGURE 3;

FIGURE 5 illustrates a configuration record for a typical network device in
5 accordance with the present invention;

FIGURE 6 illustrates in more detail the event bus shown in FIGURE 3; and

FIGURE 7 is a flow chart of a method for configuring a network device in
accordance with the present invention.

DETAILED DESCRIPTION

10 Although the present invention is open to various modifications and alternative constructions, a preferred exemplary embodiment that is shown in the drawings is described herein in detail. It is to be understood, however, that there is no intention to limit the invention to the particular forms disclosed. One skilled in the art can recognize that there are numerous modifications, equivalents and alternative
15 constructions that fall within the spirit and scope of the invention as expressed in the claims.

Referring now to FIGURE 2, there is illustrated a system 120 for configuring network devices 100, 105, 125, 130 (collectively 135) in accordance with the principles of the present invention. This embodiment includes a network manager unit 140

disposed between the administrator 110 and the network devices 135, which can include routers, optical devices, etc. The network manager unit 140 also is connected to remote storage 145 (connected by network 150) and a network manager support 155.

To alter the configuration of a network device 135 or to add a network device to an existing network, the administrator 110 can access the network manager unit 140, search for and retrieve the configuration record corresponding to a target network device, and through a series of interactive, wizard-like screens, change the configuration record for the target network device. This altered configuration record is stored in a central repository in the network manager unit 140 and can be checked against network policies accessible by the network manager unit 140. Next, the network manager unit 140 can generate device-specific commands from the new configuration record and push those device-specific commands to the target network device or have the target network device pull the commands. Finally, the network manager unit 140 can verify that the new configuration was installed correctly at the target network device.

To generate the necessary device-specific commands, the network manager unit 140 may access the remote storage device 145 that can contain the various templates needed to generate device-specific commands for different types, brands and/or models of network devices. Each of these templates can contain variable fields corresponding to either information stored in the configuration records or information input directly by the administrator. The network manager unit 140 generates the device-specific commands by retrieving the appropriate template and filling in the variable fields with the data from the configuration records and/or data input directly by the administrator

110. Once generated, these device-specific commands can be stored in the configuration record and/or they can be stored in the remote storage device 145 with an appropriate pointer stored in the configuration record.

As can be appreciated by those skilled in the art, the network manager unit 140 can be implemented on virtually any hardware system. Good results, however, have been achieved using components running the Red Hat™ LINUX Operating System and the Sun Solaris™ UNIX Operating System. In embodiments running either of these operating systems, the network manager unit 140 is configured to utilize the common services provided by that particular operating system.

Referring now to FIGURE 3, there is illustrated in more detail the network manager unit 140 shown in FIGURE 2. This embodiment of the network manager unit 140 includes six basic modules: an interface 160, a directory 165, a policy manager 170, an event bus 175, a health manager 180 and an action manager 185. The illustrated connections between the various components are exemplary only. The components can be connected in a variety of ways without changing the basic operation of the system. Although the division of the network manager unit 140 into the six components is the presently preferred embodiment, the functions of these components could be subdivided, grouped together, deleted and/or supplemented so that more or less components can be utilized in any particular implementation. Thus, the network manager unit 140 can be embodied in several forms other than the one illustrated in FIGURE 3.

Referring first to the interface module 160, it is designed to exchange data with the administrator 110 (shown in FIGURE 2) and, in some embodiments, with the network devices 135 (also shown in FIGURE 2). Although the interface 160 could implement virtually any type of interface, good results have been achieved using a graphical, web interface. Other interfaces can be based upon wireless protocols such as WAP (wireless application protocol).

The second component of the network manager unit 140 is the event bus 175. The event bus 175 includes a central posting location for receiving messages relating to network events. For example, when a configuration for a network device 135 is to be changed, an appropriate message can be published (or otherwise made available) to the event bus 175. Similarly, if a network condition such as an error occurs, an appropriate message can be published to the event bus 175. Notably, any message published to the event bus 175 can also be sent to the administrator 110 by way of the interface 160. The administrator 110, however, does not necessarily need to respond to a received message for the event to be addressed by the network manager unit 140.

To determine the proper response for a message posted to the event bus 175, the received message can be compared against the policies stored in the policy manager 170, which is a repository for the business and network policies and rules used to manage the network. By using these rules and policies, an administrator 110 (shown in FIGURE 2) can define a response for any event published to the event bus 175. The defined response can be virtually anything including reconfiguring a network device, shutting down a network device and notifying an administrator.

In operation, the policy manager 170 can read a message posted to the event bus 175. Alternatively, the event bus 175 can automatically push the message to the policy manager 170. Either way, however, the policy manager 170 uses the message to access the policy records that can be stored, for example, in a look-up table and to correlate the message to the appropriate response. Once the policy manager 170 has determined the appropriate response, that response is published to the event bus 175 as a work order that can be read by the action manager 185 and subsequently executed. That is, the action manager 185 can read the work order from the event bus 175 and perform the necessary tasks to complete that work order. In other embodiments, the work order can be sent directly to the action manager 185. For example, assume that the action manager 185 reads a work order from the event bus 175 that indicates two routers – one a Cisco™ router and one a Juniper™ router – need to be enabled. The action manager 185 can locate each of these routers and determine the device-specific code needed to enable them. The code required to enable the Cisco™ router, for example, might be “enable_router” and the code required to enable the Juniper™ router might be “router_enable.” Because the action manager 185 determines the appropriate device-specific code, however, the administrator 110 (shown in FIGURE 2) only needs to generically indicate that both devices are to be enabled. The administrator 110 does not need to know the actual device-specific code required by each router.

In other embodiments, the action manager 185 can verify that the administrator 110 (shown in FIGURE 2) has authority to make changes to network devices without authorization from additional parties. If additional authorization is required, the action manager 185 can post an appropriate message to the event bus 175.

Still referring to FIGURE 3, the directory 165 of the network manager unit 140 includes a central repository for storing the configuration records of each of the network devices connected to the network manager unit 140. For example, the directory 165 could store a separate configuration record for each of network devices 100, 105, 125 and 130 shown in FIGURE 2. In certain embodiments, several interconnected directories may be utilized, and in such systems, each directory can store a certain subset of the configuration records or a complete copy of all of the configuration records. Generally, such embodiments would employ multiple linked network manager units 140, and in the embodiment where complete copies of the configuration records are stored in different directories, synchronization techniques can be used to guarantee data integrity.

The configuration records stored in the directory 165 are searchable by way of the interface 160. That is, the administrator 110 or a component within the network manager 140 (shown in FIGURE 2) can initiate a search through the interface 160 and the results of that search can be made available to the administrator 110 through the interface 160. Moreover, the configuration records can be searched in any of a variety of ways. For example, the configuration records can be searched according to equipment type (e.g., routers, optical devices, etc.), device type (edge router, core router, etc.), device location, device manufacturer, device model, device name, operational status, etc. The directory 165 can be used to enable directory-based networking.

Referring now to the health manager 180, it can be configured to monitor the overall health of the network and/or the health of individual network devices 135

(shown in FIGURE 2) within the network. The health manager 180 can operate in an active mode and/or a passive mode. In the active mode, the health manager actively polls at least some of the network devices 135 about their status, utilization, congestion, etc. In the passive mode, the various network devices 135 automatically report to the health manager 180. In either embodiment, however, the health manager 180 can collect individual device information and model overall network health. Additionally, the health manager 180 can publish messages regarding network device problems, projected network device problems, network problems, and/or projected network problems. The policy manager 170 can then determine the appropriate course of action to take for the particular message and the action manager 185 can implement that response.

In further embodiments, the health manager can monitor the health of the network manager components. For example, the health manager can monitor the operation of the event bus, the action manager and/or the directory. Moreover, the health manager can monitor the flow of data between the various components of the network manager.

Referring now to FIGURE 4, there is illustrated in more detail the directory 165 shown in FIGURE 3. This embodiment of the directory 165 consists of four interconnected modules: configuration storage 187, configuration comparator 190, configuration reader 195 and interface 200. The directory 165, however, does not need all of the modules to function in accordance with the principles of the present invention.

The configuration reader module 195 of the directory 165 is designed to initiate communication with (or directly communicate with) a target network device and retrieve that device's actual configuration. For example, the configuration reader can retrieve the actual configuration from the memory 115 of router 105 (shown in

5 FIGURE 2). This retrieved actual configuration can then be passed to the configuration comparator 190. The configuration reader 195 can also retrieve the intended configuration of the target device from the configuration storage 187 and pass that intended configuration to the configuration comparator 190. The configuration comparator 190 can then compare the actual configuration and the intended

10 configuration and present the differences to the administrator 110 (shown in FIGURE 2). In one embodiment, the differences in the configurations are not only presented literally, but also in a natural language summary form. Once the differences have been identified, they can be used to identify a failed configuration installation and/or to aid the administrator in creating the proper configuration for a device.

15 As previously discussed, the configuration storage 187 is designed to store configuration records corresponding to network devices such as network devices 135 shown in FIGURE 2. In one embodiment the configuration storage 187 is designed not only to store the present configuration record for a network device, but also to store previous configuration records for that device. By storing these previous

20 configurations, fault recovery and correction are vastly improved over present systems because prior, successful configurations can be quickly retrieved and used to replace new, faulty configurations. For example, a prior configuration of a previously known good state can be retrieved and installed on the associated network device. This prior

configuration could be days old or even weeks old. Prior configuration records can be distinguished by version numbers and/or a time stamp. Additionally, each configuration record can include a searchable summary that includes notes on the configuration and why that configuration was modified.

5 Referring now to FIGURE 5, there is illustrated a configuration record 205 for a typical network device. This configuration record 205 is divided into four portions: a common information model ("CIM") data portion 210, a vendor data portion 215, proprietary data portion 220 and a data pointer 225. The CIM data portion 210 contains data relating to the physical attributes of a particular network device such as name,
10 device type, number of interfaces, capacity, etc. The CIM data items are defined in the CIM Specification v2.2 and the CIM Schema v2.4, both of which are well known in the art and incorporated herein by reference.

The vendor data portion 215 of the configuration record contains standard vendor-specific data regarding the particular network device. For example, the vendor
15 data portion 215 could indicate which version of an operating system that the network device is running or which features of the device are enabled. Generally, the data in the vendor data portion 215 is specific to each manufacturer and even to each model of network device.

The proprietary data portion 220 of the configuration record can contain data
20 used by the network manager unit in configuring and managing the network devices. In one embodiment, for example, the proprietary data portion 220 includes a pointer to an address at which a core dump for a network device is stored. That is, if a router

initiates a core dump, the location of that core dump could be recorded in the proprietary data portion 220 of the configuration record for that router. In other embodiments, the proprietary data portion 220 can store version numbers, time stamps, health records for a particular configuration, configuration summary data, configuration notes, etc.

The pointer portion 225 of the configuration record 205 can be used to point to a storage location where the actual device-specific commands for the associated network device are stored. Similarly, the pointer 225 could be configured to point to a storage location for a device-specific template for configuring a newly installed network device. In other embodiments, the pointer portion 225 of the configuration record can be supplemented or replaced with a storage location for actual device-specific code.

Referring now to FIGURE 6, there is illustrated in more detail the event bus 175 shown in FIGURE 3. As previously described, the event bus 175 is a posting location for messages relating to network events. Network devices as well as the other components of the network manager unit 140 (shown in FIGURE 2) can address and post events to the event bus 175.

The particular embodiment of the event bus 175 shown in FIGURE 6 is comprised of four basic modules: an interface 230, a status storage 235, an event queue 240, and an event queue manager 245. In operation, a message indicating the occurrence of a network event is posted to the event queue 240 by way of the interface 230. The messages stored at the event queue 240 are then made available to the policy

manager 170 (shown in FIGURE 3), so that a proper response can be determined. If the posted message is a work order from the policy manager 170, the work order is made available to the action manager 185 (shown in FIGURE 3) for subsequent implementation.

5 In one embodiment of the event bus 175, an event message is stored in status storage 235 along with a status field and an age field. Thus, for any message posted to the event bus 175, its status and age can be continuously monitored. (The event bus can also get messages from client devices.) For example, status storage 235 could indicate that the status for a particular event is pending in the action manager 185
10 (shown in FIGURE 3), awaiting proper authorization, completed, stalled, etc. As the status changes from one status to another, appropriate messages can be generated and posted at the event queue 240. For example, if the status of an event changes from pending to stalled, an appropriate message can be posted to the event queue 240 so that the policy manager 170 can determine how to respond. Similarly, if the age field in the
15 status storage 235 indicates that a particular network event has not been addressed within a predetermined amount of time, that event can be requeued, deleted from the event queue 240, or a new event notification indicating the delay can be generated and placed on the event queue 240.

Referring now to FIGURE 7, there is a flow chart of one method for
20 configuring or reconfiguring a network device in accordance with the principles of the present invention. In this embodiment, the administrator 110 (shown in FIGURE 2) initially logs in to the network manager unit 140 (Step 250). Through a series of a graphical interfaces, the administrator 110 can select a network device that needs to be

configured or reconfigured. The configuration record associated with the selected device can then be retrieved from the directory 165 (shown in FIGURE 3) and presented to the administrator (Step 255). If no configuration record is available for a selected device, the administrator 110 will be guided through a series of steps to build

5 the configuration for that device. Otherwise, the administrator 110 can change parameters within the configuration record of the selected device and save those altered configuration records within the directory 165 (Step 260). Notably, even though the configuration record for the selected network device has been changed, the actual configuration of the device has not been changed. Before the configuration of the

10 device can be changed, an event message indicating that a configuration record has been altered should be published to the event bus 175 (shown in FIGURE 3) (Step 265). The policy manager 170 (shown in FIGURE 3) then receives the event message, either by reading it from the event bus 175 or by receiving it from the event bus 175, and determines if the configuration change is authorized (Step 270). If the

15 configuration change is within the network rules and the administrator 110 (shown in FIGURE 2) is authorized to make the change, a work order is published to the event bus (Step 280). The action manager 185 (shown in FIGURE 3) can then read the work order from the event bus 175 and carry out the necessary steps to implement the work order (Step 280).

20 In one embodiment, the action manager 185 (shown in FIGURE 3) carries out the work order by locating the target network device, retrieving the appropriate configuration record from the directory 165 (shown in FIGURE 3), generating the device-specific code corresponding to the altered configuration (Step 290), and pushing

the device-specific code to the target network device (Step 295). The action manger
185 can also store the device-specific code in a remote storage device, such as remote
storage device 145 shown in FIGURE 2, and a pointer to the remote storage device can
be recorded in the configuration record. Finally, the action manager 185 can verify that
5 the device-specific code was properly transferred to the selected network device and
that the network device is behaving accordingly (Step 300). Assuming that the device-
specific codes were installed correctly and that the network device is operating
properly, a completion message is published to the event bus 175 (shown in FIGURE
3) (Step 305).

10 In conclusion, the present system provides, among other things, a method and
apparatus to configure, monitor and manage network devices without regard for device
type and/or manufacturer. Those skilled in the art, however, can readily recognize that
numerous variations and substitutions may be made in the invention, its use and its
configuration to achieve substantially the same results as achieved by the embodiments
15 described herein. Accordingly, there is no intention to limit the invention to the
disclosed exemplary forms. Many variations, modifications and alternative
constructions fall within the scope and spirit of the disclosed invention as expressed in
the claims.

WHAT IS CLAIMED IS:

1. A computerized method for configuring a network device, the method comprising the steps of:
 - retrieving a configuration record from a common repository of configuration
 - 5 records, the retrieved configuration record being associated with the network device;
 - modifying the retrieved configuration record;
 - storing the modified configuration record in the common repository;
 - generating at least one device-specific command corresponding to the modified configuration record; and
 - 10 transferring the generated first device-specific command to the network device.
2. The computerized method of claim 1, further comprising the step of:
 - searching the common repository for the configuration record;
 - wherein the configuration record is one of a plurality of configuration records
 - stored in the common repository.
- 15 3. The computerized method of claim 1, further comprising the step of:
 - publishing a message to an event bus;
 - wherein the published message indicates that the retrieved configuration record
 - has been modified.
4. The computerized method of claim 1, further comprising the step of:
 - 20 verifying that the modified configuration record complies with a network
 - policy.

5. The computerized method of claim 4, further comprising the step of:
publishing a work order to an event bus in response to verifying that the
modified configuration record complies with a network policy.

6. The method of claim 1, further comprising the step of:
5 verifying the successful completion of the step of transferring the generated first
device-specific command to the network device.

7. The method of claim 1, further comprising the step of:
receiving an event notification at an event bus, the event notification being
generated by the network device;
10 wherein the step of retrieving the configuration record is initiated in response to
the receiving of the event notification at the event bus.

8. The method of claim 1, wherein the step of generating the at least one
device-specific command comprises the steps of:
retrieving a device-specific command template, wherein the device-specific
15 command template comprises at least one variable field; and
populating the at least one variable field with data included in the modified
configuration record.

9. The method of claim 8, wherein the retrieved configuration record
indicates that the network device is from a particular manufacturer, and wherein the
20 retrieved device-specific command template is unique to the particular manufacturer.

10. The method of claim 8, wherein the retrieved configuration record
indicates that the network device is a particular device type and wherein the retrieved
device-specific command template is unique to the particular device type.

11. The method of claim 1, wherein the step of retrieving the configuration record comprises the step of:

retrieving the configuration record from a distributed common repository.

12. A system for configuring a network including a plurality of network devices, the system comprising:

an event posting component configured to receive a network event posting related to a first of the plurality of network devices; and

an action manager in communication with the event posting component, the action manager configured to receive the network event posting and to configure the first of the plurality of network devices in accordance with the network event posting.

13. The system of claim 12, further comprising:

a configuration storage module in communication with the event posting component, the configuration storage module configured to store at least one configuration record for each of the plurality of network devices;

wherein the action manager is configured to configure the first of the plurality of network devices by utilizing a configuration record corresponding to the first of the plurality network device.

14. The system of claim 13, wherein the configuration storage module comprises a distributed storage arrangement.

15. The system of claim 12, further comprising:

a policy manager in communication with the event posting component.

16. The system of claim 12, further comprising:

a health manager in communication with the event posting component;

wherein the health manager is configured to monitor the health of at least one of the plurality of network devices and to report the health of the at least one of the plurality of network devices to the event posting component.

17. The system of claim 12, wherein the event posting component
5 comprises:
a central posting location.

18. The system of claim 12, wherein the event posting component
comprises:

a distributed posting location.
19. The system of claim 12, further comprising:
10 a device-specific template storage module in communication with the action manager, the device-specific template storage module configured to store a plurality of device-specific command templates.

20. The system of claim 19, wherein the action manager is configured to
15 read a first of the plurality of device-specific templates from the device-specific template storage module and generate a device-specific command using the read device-specific template;

wherein the generated device-specific command is enabled to configure the first of the plurality of network devices in accordance with the network posting.

21. A system for configuring a network including a plurality of network
20 devices, the system comprising:

a configuration storage module configured to store at least one configuration record for each of the plurality of network devices; and

an action manager in communication with the configuration storage module, the action manager configured to receive an indication that a first of the configuration records has been altered, and the action manager being further configured to generate a device-specific command for a network device included in the plurality of network devices, wherein the network device corresponds to the first of the configuration records.

22. The system of claim 21, further comprising:

an event posting component configured to provide to the action manager the indication that the first of the configuration records has been altered.

10 23. The system of claim 21, further comprising:

a policy manager in communication with the event posting component.

24. The system of claim 21, further comprising:

a device-specific template storage module in communication with the action manager, the device-specific template storage module configured to store a plurality of device-specific command templates;

wherein at least a first of the plurality of device-specific command templates is usable by the action manager to generate the device-specific command for the network device.

25. A system for configuring a network device, the system comprising:

20 at least a first processing element configured to execute instructions;

at least a first memory device electronically coupled with the at least a first processing element; and

a plurality of instructions stored on the memory device, the plurality of instructions configured to cause the at least a first processing element to perform the steps of:

- retrieving a configuration record from a common repository of
- 5 configuration records, the retrieved configuration record being associated with the network device;
- modifying the retrieved configuration record;
- storing the modified configuration record in the common repository;
- generating at least a first device-specific command corresponding to the
- 10 modified configuration record; and
- transferring the generated first device-specific command to the network device.

26. The system of claim 25, wherein the plurality of instructions are further configured to cause the at least a first processor to perform the step of:

- 15 searching the common repository for the configuration record;
- wherein the configuration record is one of a plurality of configuration records stored in the common repository.

27. The system of claim 25, wherein the plurality of instructions are further configured to cause the at least a first processor to perform the step of:

- 20 publishing a message to an event bus;
- wherein the published message indicates that the retrieved configuration record has been modified.

28. The system of claim 25, wherein the plurality of instructions are further configured to cause the at least a first processor to perform the step of:

verifying that the modified configuration record complies with a network policy.

29. The system of claim 28, wherein the plurality of instructions are further configured to cause the at least a first processor to perform the step of:

5 publishing a work order to an event bus in response to verifying that the modified configuration record complies with a network policy.

30. The system of claim 28, wherein the plurality of instructions are further configured to cause the at least a first processor to perform the step of:

10 verifying the successful completion of the step of transferring the generated first device-specific command to the network device.

31. The system of claim 25, wherein the plurality of instructions are further configured to cause the at least a first processor to perform the step of:

receiving an event notification at an event bus, the event notification being generated by the network device;

15 wherein the step of retrieving the configuration record is initiated in response to the receiving of the event notification at the event bus.

32. The system of claim 25, wherein the plurality of instructions are configured to cause the at least a first processor to generate the at least a first device-specific command by:

20 retrieving a device-specific command template, wherein the device-specific command template comprises at least one variable field; and

populating the at least one variable field with data included in the modified configuration record.

33. The system of claim 32, wherein the retrieved configuration record indicates that the network device is from a particular manufacturer and wherein the retrieved device-specific command template is unique to the particular manufacturer.

34. The system of claim 32, wherein the retrieved configuration record
5 indicates that the network device is a particular device type and wherein the retrieved device-specific command template is unique to the particular device type.

35. The system of claim 25, wherein the plurality of instructions are configured to cause the at least a first processor to perform the step of retrieving the configuration record by:

10 retrieving the configuration record from a distributed common repository.

36. A system for configuring a network device, the system comprising:
means for retrieving a configuration record from a common repository of
configuration records, the retrieved configuration record associated with the network
device;

15 means for modifying the retrieved configuration record; and
means for storing the modified configuration record in the common repository.

37. The system of claim 36, further comprising:
means for generating at least a first device-specific command corresponding to
the modified configuration record; and

20 means for transferring the generated first device-specific command to the
network device.

1 / 7





FIG. 1

2 / 7

120
N



3 / 7

140

N




FIG. 3

4/7

165

N




FIG. 4

5 / 7

205

N




FIG. 5

6 / 7


175
N

FIG. 6

7 / 7




FIG. 7.

This Page Blank (uspto)

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☒ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.

This Page Blank (uspto)